



www.saberindustrial.com

sales@saberindustrial.com

+961-9-546 540



APPENDING OF



^{SUPER} STRONG ADHESIVE For lasting décor



⁹⁰⁰SKIRTING-BOARDS, FLOOR PAN^{EL} ^{ECO}RATIVE STYROFOAM, THERMAL AN ^{COUSTIC} INSULATION MATERIALS ^{OL} ⁹⁰¹STYRENE AND POLYURETHANE FOM



DÉCOR ADHESIVE

DYNA-FIX [®] Décor Adhesive is a super strong one component mounting adhesive with exceptional initial grip for heavy assembly. Does not require mechanical fixing and for INTERNAL and EXTERNAL use. Paintable, anti-mold, solvent free, odorless... It is specifically designed for bonding decorative polystyrene and polyurethane foam elements to absorbent surfaces such as concrete, plaster chipboard, wood, plasterboard, gypsum. It is particularly suitable for fixing insulating and decorative panels, wooden panels, beads, skirting boards, rosettes, plaques etc.

1/2



DYNA-FIX®

www.saberindustrial.com

sales@saberindustrial.com

+961-9-546 540

Features

- Replaces fixings
- Internal / external use
- Anti mold
- Paintable
- Solvent free
- Odorless



Technical Data

Property	Unit	Value
Temperature Resistance	°C	-30 to +80
Application Temperature	°C	+5 to +40
Workability Time	minutes	10
Compatibility with Paint	S. 11	Compatible

Surface Preparation

Surfaces must be clean, dry and free from grease, dust and frost. Extrude Décor Adhesive with a caulking gun to one of the parts and join by pressing forcefully and evenly. The parts may be repositioned within 5 minutes.

At least one of the surfaces must be porous. On skirting boards and tiles apply to glue points, on beads and panels apply to "X", in straight or wavy strips, to better develop the initial grip. It is not recommended for use on unpainted surfaces, on bituminous surfaces, for applications in permanent contact with water or with humidity.





SUBSTRATES MUST BE CLEAN, DRY AND FREE OF DUST

PLACE CARTIDGE IN A GUN SCREW NOZZLE AND CUT TIP TO OBTAIN ADEQUATE OPENING



Shelf Life

16 months from date of production, when stored at or below 30°C in the original unopened container

Packaging

Standard Colors

- 280 / 300 mL cartridge
- 5 L pale

The information is offered in good faith and is believed to be accurate. It should not however be used in substitution for customer's tests to ensure that DYNA-FIX® products are safe, effective and compatible for the intended use. Sole warranty is that the product will meet the DYNA-FIX® sales specifications in effect at the time of delivery. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.



Designed & Manufactured According to AFAQ ISO 9001:2015 Certified Quality Management System

Saber Industrial Corporation – Industrial Zone, Jbeil Edde, LEBANON

Version 4.0 - Revised 2021