

PROFESSIONAL **INTERIOR & EXTERIOR** SEALANT FOR LARGE GAP-FILLING PROJECTS FOR MOUNTING, INSULATING, FILLIN Staling Windows, Doors, Pipe Racks, Holes. Good Adhesion WCRETE, BRICK, PLASTER, FOA OLYSTYRENE, PVC, METAL AND W 750 ml

Product Description

High Quality Self-Expanding PU Foam for Int./Ext. bonding, fixing, mounting, filling, insulating & sealing applications. Mold-proof, paintable. Excellent thermal & acoustic insulation.

Approvals



Features

- Quick and easy to apply
- Excellent adhesion to most building material
- Thermal & Acoustical Insulation
- Vibration and shock resistant
- Moisture / Mold resistant
- Ozone friendly (propellants CFC and HCFC free)
- Resistant to temperature extremes -30°C to +80°C
- Ageing Resistant







WATER RESISTANT

AGEING [.] RESISTANT

TEMPERATURE RESISTANT

PAINTABLE









TECHNICAL DATA SHEET Version 2.0 – Revised 2025

Packaging



/box

750 mL Can

/ pallet

Area and a second
120 boxes
/ nallat

Technical Data

Property	Unit	Value
Chemical Base		Polyurethane
Color		Light Yellow
Density	g/cm ³	0.011 - 0.017
Cutting Time	Min	20 – 30
Tack Free Time	Min	6 - 10
Compression Strength	КРа	25.00
Tensile Strength	КРа	35.70
Application Temperature	₀ C	+5 to +35
Temperature Resistance	º C	-30 to +80

Shelf Life



+ 27°C 5°C

Proper

Storage

15 Months



Shake the can very well. Remove protective cap, screw on the nozzle. Apply with the can upside down.



Surface Preparation

Surfaces must be clean, dry and free from grease, dust and frost. In case of renovation work, old sealant as well as old paints must be removed completely. Can should be at room temperature (may be achieved by immersing in warm – NOT hot water).

The information in this document is based on Saber Industrial's technical and practical experience. It is provided for reference only and may not include all relevant details. Users must test product suitability for their intended application, surface, and conditions. Saber Industrial accepts no liability for misuse, improper application, storage, or transport. We reserve the right to change formulations without notice. Warranty is limited to conformance with current sales specifications. Liability is restricted to refund or replacement of non-conforming product.

