



DYNA-FIX®

www.saberindustrial.com

sales@saberindustrial.com

+961-9-546 540



PROFESSIONAL MEGA FOAM

DYNA-FIX® Professional Mega Foam is a high-quality, one component, self-expanding, ready-to-use polyurethane foam for large gap-filling projects. Suitable for use on all building material for the purpose of bonding, mounting filling, insulating and sealing. Foam expands to fill gaps and cured excess may be cut and sanded. Cured foam is mold proof and paintable.



Features

- Quick and easy to apply
- Excellent adhesion to most building material
- Thermal & Acoustical Insulation
- Vibration and shock resistant
- Moisture / Mold resistant
- Ozone friendly (propellants CFC and HCFC free)
- Resistant to temperature extremes -50°C to +90°C
- Ageing Resistant



Surface Preparation

Surfaces must be clean, dry and free from grease, dust and frost. In case of renovation work, old sealant as well as old paints must be removed completely. Can should be at room temperature (may be achieved by immersing in warm – NOT hot water).

Instructions

Shake the can very well. Remove protective cap, screw onto gun. Apply with the can upside down filling 30% – 70% (to allow for expansion). For gaps wider than 5cm, fill gradually by layers. Uncured foam may be cleaned with acetone. Allow to cure. After curing, excess may be removed mechanically, and the cured foam should be protected against UV radiation.



Designed & Manufactured According to AFAQ
ISO 9001:2015 Certified Quality Management System

Technical Data

Property	Unit	Value
Density	g/cm ³	0.018 – 0.022
Yield for 750ml	L	Up to 65
Cutting time @23°C to 30°C	Min	20
Temperature Resistance	° C	-50 to +90

Priming

This product features adhesion to a variety of non-porous substrates; however, for specific substrates, priming may be necessary to improve adhesion. Please consult our Technical Service Department. Surface should be dampened.

Shelf Life

15 months from date of production, when stored at or below 25°C in the original unopened container

Packaging

- 750 mL can

The information is offered in good faith and is believed to be accurate. It should not however be used in substitution for customer's tests to ensure that DYNA-FIX® products are safe, effective and compatible for the intended use. Sole warranty is that the product will meet the DYNA-FIX® sales specifications in effect at the time of delivery. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.