



# DYNA-FIX®

www.saberindustrial.com

sales@saberindustrial.com

+961-9-546 540



## HIGH STRENGTH THREADLOCKER

Permanent, high strength anaerobic thread locker that cures in the absence of air between close-fitting metal surfaces.

**DYNA-FIX® High Strength Threadlocker** prevents vibration, loosening & leakage, locks threaded joints, nuts, screws & studs, & withstands shocks & vibrations.



## Features

- Permanent High Strength
- Prevents Corrosion
- Excellent Shock & Vibration resistance

## Surface Preparation

Surfaces must be clean, dry and free of grease, dust, oil and any contaminant to ensure that the bonding process is not compromised.

## Instructions

Apply with a 360 turn to the first three threads of both male & female fittings.

Wipe off excess jointing compound in the direction of the thread using an absorbent tissue paper.

Assemble parts and hold on for 24 hours until full curing is reached.

For disassembly, hand tools should be used to remove mating parts. Heat may be applied if needed.

## Technical Data

Property	Unit	Value
Overall Appearance	Low viscosity, Red Liquid	
Flash Point (ASTM D56-05)	°C	>90
Temperature Range	°C	-50 to +180
Gap Filling	Mm	<0.15
Shock Resistance		Excellent
Vibration Resistance		Excellent

## Shelf Life

24 months from date of production, when stored at or below 25°C in the original unopened container

## Packaging

- 50 mL bottle



Designed & Manufactured According to AFAQ  
ISO 9001:2015 Certified Quality Management System

*The information is offered in good faith and is believed to be accurate. It should not however be used in substitution for customer's tests to ensure that DYNA-FIX® products are safe, effective and compatible for the intended use. Sole warranty is that the product will meet the DYNA-FIX® sales specifications in effect at the time of delivery. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.*