









www.saberindustrial.com

sales@saberindustrial.com

+961-9-546 540

Features

- · Applied with standard caulking gun
- Economical injection system (reduced drilling diameter)
- Anchors may be placed close to free edges
- Variable embedment depths
- Ratio of 10:1










Installation Instructions



Loading & Curing Times

Substrate Temperature (° C)	Working Time (Mins)	Loading Time (Mins)
+5 to +10	12	120
+10 to +20	6	80
+20 to +25	4	40
+25 to +30	3	30
+30 to +35	2	20
+35 to +40	1.5	15
+40	1.5	10

Installation Parameters

*Design Load equals to Characteristic Load divided by a factor of 1.8

Anchor Size	Drill Hole Dia.	Minimum Embedment Depth	Maximum Embedment Depth
M8	10 mm	64 mm	96 mm
M10	12 mm	80 mm	120 mm
M12	14 mm	96 mm	144 mm
M16	16 mm	128 mm	192 mm
M20	22 mm	160 mm	240 mm
M24	26 mm	192 mm	288 mm

Shelf Life

15 months from date of production, when stored at or below 25°C in the original unopened container



Designed & Manufactured According to AFAQ ISO 9001:2015 Certified Quality Management System

Packaging

• 300 mL cartridge

The information is offered in good faith and is believed to be accurate. It should not however be used in substitution for customer's tests to ensure that DYNA-FIX® products are safe, effective and compatible for the intended use. Sole warranty is that the product will meet the DYNA-FIX® sales specifications in effect at the time of delivery. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.