



## HIGH TEMP MASKING

Premium quality **high temperature** masking tape with excellent conformability. Manufactured with crepe paper and solvent based natural rubber adhesive. Ideal product for industrial use and in applications requiring high temperature exposure as in automotive oven painting. May also be used in other masking applications, packaging, labeling, bundling etc...



## Features

- High temperature application product
- Excellent adhesion on all surfaces
- For retouching processes on automobiles and body shop works with temperatures up to 90°C
- Hand tearable
- Unrolls clean with no splitting and tearing
- Sharp color edge
- Resistant to water, oil and solvents
- High conformability allowing curving and adhesion on irregular surfaces
- Clean, Residue-free removal

## Instructions

Apply on clean surfaces to be masked. When removing, pull tape diagonally rather than straight up. Do not expose to temperatures above 90°C and UV.

## Standard Widths

- 18 mm
- 24 mm
- 48 mm
- Custom widths available upon request

## Standard Colors



Designed & Manufactured According to AFAQ  
ISO 9001:2015 Certified Quality Management System

## Technical Data

Property	Unit	Value
Total Weight	g/m <sup>2</sup>	82 ± 3
Total Thickness	Microns	127 ± 15
Steel Adhesion (ASTM D 3330)	oz/in	24.7
Elongation (ASTM D3759)	%	10 ± 4
Tensile strength (ASTM D3759)	kg/in	7.2~9.9
Initial tack (PSTC-6)	mm	< 100
Maximum temperature resistance	°C	90
Application temperature	°C	10 to 55

## Storage Information

Store in a cool dry place away from heat source and sunlight at a temperature of 5°C to 25°C and relative humidity of about 50%.

## Shelf Life

18 months from date of production, when stored at or below 30°C in the original unopened container

*The information is offered in good faith and is believed to be accurate. It should not however be used in substitution for customer's tests to ensure that DYNA-PRO® products are safe, effective and compatible for the intended use. Sole warranty is that the product will meet the DYNA-PRO® sales specifications in effect at the time of delivery. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.*