

RAINFOOF ACRYLIC WEATHER SEALANT

TECHNICAL DATA SHEET
Version 7.0 – Revised 2025



Product Description

Professional Acrylic Weather Sealant for Int./Ext. use in connecting and perimeter pointing on most building material. Excellent adhesion, paintability, flexibility, slump resistance. Quick skinning/drying.

Approvals



Features

- Indoor & Outdoor Use
- Paintable 3 hours after application
- Good UV Resistance
- Ageing Resistance
- Solvent Free (water-based)



**WEATHER
RESISTANT**



**UV
RESISTANT**



**PERMANENTLY
ELASTIC**



**SUPERIOR
ADHESION**



PAINTABLE




RAINPROOF ACRYLIC WEATHER SEALANT

TECHNICAL DATA SHEET
Version 7.0 – Revised 2025




Packaging



Technical Data


Property	Unit	Value
Chemical Base		Acrylic
Tack free time	Min	15 – 30
Density	g/mL	1.55 – 1.65
Tensile Strength	MPa	0.70
Elongation at Break	%	> 325
Application Temperature	°C	+5 to +40
Temperature Resistance	°C	-30 to +80

Shelf Life



Instructions

This sealant is ready to use. After suitable joint preparation and masking, the sealant is gunned into place and tooled within 5 minutes, using a spatula which has been dipped in soapy water. Remove masking tape immediately after tooling. If necessary, clean uncured material using an approved sealant remover. For removal of cured material, abrasion or other mechanical means may be needed.



Standard Colors



Surface Preparation

Surfaces must be clean, dry and free of grease, dust and frost. In case of renovation work, old sealant as well as old paint must be removed completely.

Priming

This product features adhesion to a variety of non-porous substrates; however, for specific substrates, priming may be necessary to improve adhesion. Please consult our Technical Service Department.

The information in this document is based on Saber Industrial's technical and practical experience. It is provided for reference only and may not include all relevant details. Users must test product suitability for their intended application, surface, and conditions. Saber Industrial accepts no liability for misuse, improper application, storage, or transport. We reserve the right to change formulations without notice. Warranty is limited to conformance with current sales specifications. Liability is restricted to refund or replacement of non-conforming product.