



ALUMINUM SPRAY PAINT



DYNA-PRO® Aluminum Profile Paint is a high performance Eloxal spray paint available in a wide range of standard and custom colors. Ideal for use in touch up jobs requiring exact color matching for the repair of scratches on eloxated surfaces like doors, window frames, shower cubicles, aluminum, metal, glass etc. Product is user-friendly, with a tamper-proof cap for added security.

DYNA-PRO® Aluminum Profile Paint sprays are 100 % free of heavy metals and contain CFC-free propellants. The caps are made of recyclable material. All DYNA-PRO® spray products comply with the latest international labeling regulations and approval criteria.

Features

- Ideal for Touch-up applications
- Exact color matching
- High quality
- Rapid drying
- Resistant to weather and thinned detergents
- No CFCs



Surface Preparation

Surfaces must be clean, dry and free from grease and dust. Smooth off uneven surfaces. Prime with a primer suitable for the surface to be painted. It may be necessary to carry out a spray test on an inconspicuous section to check the compatibility of the paint.

Instructions

Shake the can for 2 minutes before using. Spray at a distance of about 25cm. Allow to dry as specified. May be polished after 48 hours. Make sure to protect surfaces adjacent to the surface to be sprayed from spray mist using Dyna-Pro® high quality masking tape.

Can Coverage

Approximately 0.4 m² per 150 ml can. Exact coverage and number of coats required depends on the color being used

Technical Data

Property	Unit	Value
Dust dry	Min	10
Dry to touch	Min	30
Full drying time	Hours	24
Ideal Application Temperature	°C	10 – 27

Hazardous Identification

Apply in well ventilated places only. Do not spray onto surfaces painted with synthetic resin paints. The product is extremely flammable, an irritant to eyes and water polluting. In use, may form flammable / explosive vapor-air mixture. Do not store together with pyrotechnic substances. Do not pierce or burn the can even after use.

Shelf Life

60 months from date of production, when stored at or below 30°C in the original unopened container

Packaging

- 150 mL cans

Standard Colors



Designed & Manufactured According to AFAQ
ISO 9001:2015 Certified Quality Management System

The information is offered in good faith and is believed to be accurate. It should not however be used in substitution for customer's tests to ensure that DYNA-PRO® products are safe, effective and compatible for the intended use. Sole warranty is that the product will meet the DYNA-PRO® sales specifications in effect at the time of delivery. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.