



www.saberindustrial.com

ERIES

sales@saberindustrial.com

+961-9-546 540



POWERFUL FAST ACTING FORMULA CITALYTIC CONVERTER AND OXYGEN SENSOR SHE CLEANS WITHOUT DISMANTLING AND DISASSEMBLY IMPROVES ENGINE PERFORMANCE AND FUEL ECONOMY HELPS IN EASY ENGINE STARTING

400ml

CARBURETOR CLEANER

Dyna-Pro® Carburetor Cleaner is an effective spray that successfully loosens and removes gum, varnish and dirt which accumulate over time and clog carburetors and choke valves.

It quickly removes these deposits from the inside and outside of the carburetor to improve engine performance and fuel economy. It also effectively cleans all non painted metal parts and surfaces.

Dyna-Pro® Carburetor Cleaner is used in the routine cleaning of carburetors, manual and automatic choke valves, linkages and manifold heat controls. It may also be used to clean other non-painted metal parts and surfaces. For best results, carburetors should be cleaned twice per year.

1/2



DYNA-PRO®

www.saberindustrial.com

sales@saberindustrial.com

+961-9-546 540

Features

- Fast acting formula with powerful solvents
- Catalytic converter and oxygen sensor safe.
- Residue free spray
- Cuts through varnish, gum and carbon build up
- Loosens sediments
- Dissolves dirt, gung and sludge
- Removes glue, grease and charcoal
- Effective cleaning without need to disassemble
- Improves engine performance and fuel economy
- Helps in easy engine starting

Application

- 1. Use appropriate protective wear including gloves and eye protection
- Shake can vigorously before use. The can should be at room temperature, away from sunlight
- 3. Protect painted surfaces from overspray using appropriate masking
- Spray Dyna-Pro[®] Carburetor Cleaner directly onto the area to be cleaned inside and outside the carburetor to loosen gung and dirt
- 5. Using shop rags wipe away instantly
- You may need to start the engine and reapply spray as necessary
- 7. Apply spray only in well ventilated environments
- 8. Keep in cool, dry place, away from sunlight
- 9. Toss empty can in trash.

Technical Data

Property	Unit	Value
Color		Transparent liquid
Odor		Solvent odor
pH value		Neutral
Density at 20ºC	g/ml	0.90 ± 0.01
Inside pressure at 20°C	MPa	0.50 ± 0.05
Solubility	1	Insoluble in water
Emission rate	%	≥ 98

Shelf Life

36 months from date of production, when stored at or below 30°C in the original unopened container

Packaging

• 400 mL can

Caution

HIGHLY FLAMMABLE

Can contents under pressure. Do not puncture or burn.

Do not place in hot water or near other sources of heat such as stoves & radiators. Use only in well-ventilated areas.



The information is offered in good faith and is believed to be accurate. It should not however be used in substitution for customer's tests to ensure that DYNA-PRO® products are safe, effective and compatible for the intended use. Sole warranty is that the product will meet the DYNA-PRO® sales specifications in effect at the time of delivery. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.



Designed & Manufactured According to AFAQ ISO 9001:2015 Certified Quality Management System