




PVC ELECTRICAL INSULATING TAPE

Premium quality PVC insulating tape with excellent adhesion, and high water/solvent resistance providing great electrical insulation for all wire and cable splices. Clean, residue free removal. Highly stretchable and conformable. High dielectric strength and good mechanical protection. Available in a wide range of colors for easy identification.



Features

- Excellent Adhesion
- High Water/Solvent Resistance
- High Insulation
- Clean, Residue Free Removal
- Highly Stretchable/Conformable
- High Dielectric Strength
- Good Mechanical Protection
- Indoor/Outdoor Application



Instructions

Surfaces should be clean of dust, grease, oil or any other contaminants.

To ensure optimal bonding, tape should be applied with sufficient tension and a minimum of two layers with a half overlap. The final layer should be wrapped with no tension to prevent flagging effects.

Standard Colors

- Black
- White
- Grey
- Red
- Blue
- Yellow

Technical Data

Property	Unit	Value
Backing		PVC Film
Total Thickness	mm	0.13
Elongation	%	140
Tensile Strength	kg / 25 mm	4
Dielectric Strength	kV	5
Adhesion to Stainless Steel	Kg / 25 mm	0.4
Temperature Resistance	°C	0 - 90

Storage Information

Store in a cool dry place away from heat source and sunlight at a temperature of 5°C to 25°C and relative humidity of about 50%.

Shelf Life

12 months from date of production, when stored properly.



Designed & Manufactured According to AFAQ
ISO 9001:2015 Certified Quality Management System

The information is offered in good faith and is believed to be accurate. It should not however be used in substitution for customer's tests to ensure that DYNA-PRO® products are safe, effective and compatible for the intended use. Sole warranty is that the product will meet the DYNA-PRO® sales specifications in effect at the time of delivery. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.