



# DYNA-PRO®

www.saberindustrial.com

sales@saberindustrial.com

+961-9-546 540



## GREASE SPRAY

**Dyna-Pro® Lithium Grease Spray** is a high-quality all-purpose grease that is supplied in an aerosol can for ease of use and convenience. Its tacky, lubricating formula does not freeze nor melt. It therefore lubricates by creating a protective barrier guarding against moisture and oxidation, even in extreme temperatures. It is also highly resistant to salt corrosion. It reduces friction, rust and corrosion.

**Dyna-Pro® Lithium Grease Spray** is an ideal easy to use lubricant for several materials including steel and plastics. It is used on moving parts such as doors, locks, rubber gaskets, motors, hinges, cables, gears, chains, springs etc.. A trial test on a small section is recommended before use.

## Features

- Low odor
- Fast acting
- Easy to apply
- Quick drying
- Low friction lubrication
- Heavy duty protection
- Operates well in temperature extremes
- Prevents rust and eliminates humidity

## Application

1. Shake can vigorously before use. The can should be at room temperature, away from sunlight
2. Remove greasy residues with shop cloth
3. Spray Dyna-Pro® Grease directly onto the area to be lubricated or treated
4. Apply spray only in well ventilated environments
5. Keep in cool, dry place, away from sunlight
6. Dispose of empty can suitably.
7. Do not puncture can or subject it to high heat or flame.
8. Do not expose to temperature above +50°C

## Technical Data

Property	Unit	Value
Color		White viscous paste
Odor		Lemon
Density at 20°C	g/ml	0.70
Inside pressure at 20°C	MPa	0.45 ±0.05
Volatilization residue	%	45
Emission rate	%	≥90

## Shelf Life

36 months from date of production, when stored at or below 30°C in the original unopened container

## Packaging

- 400 mL can

## Caution

**HIGHLY FLAMMABLE**

Can contents under pressure. Do not puncture or burn.

Do not place in hot water or near other sources of heat such as stoves & radiators.

Use only in well-ventilated areas.



Designed & Manufactured According to AFAQ  
ISO 9001:2015 Certified Quality Management System

*The information is offered in good faith and is believed to be accurate. It should not however be used in substitution for customer's tests to ensure that DYNA-PRO® products are safe, effective and compatible for the intended use. Sole warranty is that the product will meet the DYNA-PRO® sales specifications in effect at the time of delivery. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.*