



# DYNA-PRO®

www.saberindustrial.com

sales@saberindustrial.com

+961-9-546 540



## SILICONE SPRAY

Superior quality transparent silicone spray used to lubricate moving parts and preserve plastic or rubber parts from corrosion and moisture. It prevents freezing, drying out, creaking and squeaking.

**Dyna-Pro® Silicone Spray** is used on moving parts such as doors, locks, rubber gaskets, motors, exercise equipment, vending machines, industrial machinery, springs and more.

## Features

- Quick to dry
- Water repellant
- Weather resistant
- Weak acids & bases resistant
- Excellent mechanical & thermal stability
- Excellent adhesion
- Directed jet spray
- Interior / Exterior usage
- Prevents rust and eliminates humidity

## Application

1. Surfaces must be clean, dry and free from grease, dust and frost.
2. Shake can vigorously before use. The can should be at room temperature, away from sunlight
3. Hold the can approximately 15-30 cm from the object to be sprayed. In a well-ventilated area, press the spray button firmly while moving can back and forth.
4. Apply silicone spray in a thin layer and do not apply continuous spray.
5. After use, clear out the can's nozzle. To do so, hold the can upside down, depress the nozzle and keep spraying until only gas emerges.
6. Toss empty can in trash.

## Technical Data

| Property                | Unit | Value      |
|-------------------------|------|------------|
| Color                   |      | Colorless  |
| Odor                    |      | Lemon      |
| pH Value                |      | Neutral    |
| Density at 20°C         | g/ml | 0.74       |
| Inside pressure at 20°C | MPa  | 0.45 ±0.05 |
| Volatilization residue  | %    | 8          |
| Emission rate           | %    | ≥92        |

## Shelf Life

36 months from date of production, when stored at or below 30°C in the original unopened container

## Packaging

- 400 mL can

## Caution

**HIGHLY FLAMMABLE**

Can contents under pressure. Do not puncture or burn.

Do not place in hot water or near other sources of heat such as stoves & radiators.

Use only in well-ventilated areas.



Designed & Manufactured According to AFAQ  
ISO 9001:2015 Certified Quality Management System

*The information is offered in good faith and is believed to be accurate. It should not however be used in substitution for customer's tests to ensure that DYNA-PRO® products are safe, effective and compatible for the intended use. Sole warranty is that the product will meet the DYNA-PRO® sales specifications in effect at the time of delivery. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.*