



DYNA-PRO®

www.saberindustrial.com

sales@saberindustrial.com

+961-9-546 540



SPRAY PAINT

Long lasting spray paint for coating interior/exterior surfaces providing excellent coverage. Used on construction materials, decorative elements & for advertisement purposes. Available in a wide color variety.



INTERIOR/
EXTERIOR USE



EASY TO APPLY



HIGH COVERAGE



QUICK DRY



CFC FREE



Features

- Quick to dry
- Easy to apply
- Weather resistant
- High coverage
- Interior/Exterior application
- CFC free
- Superior adhesion

Application

For interior or exterior coating of surfaces such as wood, steel, iron, aluminum alloy, galvanized steel and other metal surfaces.

Widely used on a variety of construction materials, decorative items & for advertisement purposes.

Preparation

Shake can vigorously for at least one minute after rattling of mixing ball is heard. While in use, shake intermittently to ensure color uniformity and to prevent clogging.

Hold the can approximately 30 cm from the object to be sprayed. Press spray button firmly while moving can back and forth. Finger must not protrude over front edge of spray button at any time.

Keep can in a level line with surface and do not apply continuous spray.

For best results, apply 2 to 3 thin coats with intermittence of 10 minutes

If product bubbles, foams or runs then you are too close to the surface or coat is too heavy.

After use, clear out the nozzle by holding the can upside down and spraying until only gas emerges. Toss empty can in trash.

Do not puncture can or subject to high heat or flame.

Technical Data

Property	Unit	Value
Dust dry	Min	10
Dry to touch	Min	30
Full drying time	Hours	24
Ideal Application Temperature	°C	10 – 27

Safety Precautions

Keep away from children

Keep upright

Shelter from direct sunlight

Do not store at temperatures exceeding 50°C

Do not pierce or burn even when empty

Do not smoke during the spraying process

For safety reasons, please wear protective gloves as well as goggles before using Spray paint, and do not draw them off before the whole procedure is finished.

Can contents under pressure. Do not puncture or burn.

Do not place in hot water or near other sources of heat such as stoves & radiators.

Use in well-ventilated areas only.

Shelf Life

36 months from date of production, when stored at or below 30°C in the original unopened container

Packaging

- 400 mL can

Standard Colors



The information is offered in good faith and is believed to be accurate. It should not however be used in substitution for customer's tests to ensure that DYNA-PRO® products are safe, effective and compatible for the intended use. Sole warranty is that the product will meet the DYNA-PRO® sales specifications in effect at the time of delivery. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.



Designed & Manufactured According to AFAQ
ISO 9001:2015 Certified Quality Management System