



## GOLD ACETOXY SILICONE

**ELASTO® Gold** is a one-part, *medium modulus, anti-fungal, acetoxy* curing silicone sealant for general purpose applications. Very good adhesion and assembly of non-porous material, such as glass, metal, tiles, wood, concrete and some plastics. It is especially suitable in applications where there is exposure to humidity, such as kitchens and bathrooms due to its anti-fungal capabilities that prevent the growth of mold on the sealant

### Approvals



<b>CE</b>
SABER INDUSTRIAL CORPORATION 14 DoP-ELASTOG-AX-01
EN 15651 – 3: S Class S1



## Features

- Acetoxy Curing
- Medium Modulus
- Anti-fungal
- Excellent adhesion
- Resistant to ozone, ultraviolet radiation and temperature extremes





## Surface Preparation

Surfaces must be clean, dry and free from grease, dust and frost. In case of renovation work, old sealant as well as old paint must be removed completely. Surface should be cleaned with a suitable solvent for the substrate such as ELASTO® Silicone Cleaner, isopropanol etc.

## Instructions

This sealant is ready to use. After suitable joint preparation and masking with a general-purpose masking tape such as Elasto®, the sealant is gunned into place and tooled within 5 minutes, using a spatula which has been dipped in soapy water. Remove masking tape immediately after tooling. If necessary, clean uncured material using an approved sealant remover. For removal of cured material, abrasion or other mechanical means may be needed.



Designed & Manufactured According to AFAQ  
ISO 9001:2015 Certified Quality Management System

## Technical Data

Property	Unit	Value
Extrusion Rate 20°C 6.2Kg/cm2	g/min	228
Tack-free time at 23°C	Min	15
Skin Over Time	Min	14
Durometer Shore A, 3d/RT	Mpa	>= 18
Tensile 3d/RT	%	>= 1,55
Elongation, 3d/RT	%	>= 450
Elongation	%	570
Joint Movement Capability	Mpa	25

## Priming

This product features adhesion to a variety of non-porous substrates; however, for specific substrates, priming may be necessary to improve adhesion. Please consult our Technical Service Department.

## Shelf Life

14 months from date of production, when stored at or below 25°C in the original unopened container.

## Packaging

- 280 / 300 mL cartridge

## Standard Colors



*The information is offered in good faith and is believed to be accurate. It should not however be used in substitution for customer's tests to ensure that ELASTO® products are safe, effective and compatible for the intended use. Sole warranty is that the product will meet the ELASTO® sales specifications in effect at the time of delivery. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.*